



American Liberty

PRODUCT SPECIFICATION

Flooring can be installed Residential, Light-Commercial and 3-Seasons Room applications by following the recommendations outlined in the installation instructions.

Product Performance & Technical Data

Classification	ASTM F3261-20 Class I Type B Solid Vinyl Floor Tile	
• Castor Chair Test	EN 425	PASS
• Chemical Resistance	ASTM F925 NALFA 3.4	PASS
• Critical Radiant Flux	ASTM E648	PASS
• Dimensional Stability	ASTM F2199	PASS
• Flexural Strength	ASTM D790	PASS
• HIIC	ASTM E3222	59
• Impact Sound	ASTM F1265	PASS
• IIC	ASTM E989	58
• Overall Thickness	ASTM F386	PASS
• Residual Indentation	ASTM F1914	PASS
• Resistance to Heat	ASTM F1514	PASS
• Resistance to Light	ASTM F1515	PASS
• Static Load Limit	ASTM D970	PASS
• Sound Test	ASTM E90. E492	PASS
<i>(8 inch concrete slab no drop ceiling)</i>		
• STC	ASTM E413	53
• Tabor Abrasion Test	ASTM D4060	PASS
• FloorScore® Certification	# SCS-FS-07267	

Product Details

- Overall Thickness 5.5 mm
- Composite Rigid Core Thickness 4.5 mm
- Wearlayer Thickness 20 mil
- Pad Type/Thickness XPO 1.0 mm
- Plank Size 7.69" x 60"
- Finished Coating Ceramic Urethane
- Embossing Overall
- Edge Type Painted Bevel
- Installation Type Uniclic Angle/Angle

Packaging Information

- Square Feet per Carton 28.84
- Planks per Carton 9
- Cartons per Pallet 55
- Lbs. per Carton 39.07

Warranty

For complete details, refer to the Warranty Information Sheet

- 30 Year Residential Limited Warranty
- 15 Year Light Commercial Limited Warranty
- 10 Year 3-Seasons Room Limited Warranty



Installation Details
lvinstallation.com