

TECHNICAL INFORMATION & SPECIFICATIONS

GALLERY 5.0mm

**RECYCLABLE
100% PVC-FREE**

PRODUCT INFORMATION

CONSTRUCTION	100% Polypropylene (PPMD60)	Reinforced with Natural Mineral Powder
THICKNESS	5 mm nominal	4mm + 1mm attached pad
PLANK DIMENSIONS	1290 mm x 203 mm	50.79" x 7.992"
PLANKS PER CARTON / SF	9 planks	25.37 SF
INSTALLATION SYSTEM	Glueless click	Angle-Angle
EDGE DETAIL	Micro-Bevel Edge	
FINISH / WEAR LAYER	Sealtec Plus	
DENSITY	1 Plank = 0.71 kg	1,272 kg/m ³ / 79.41 lbs/ft ³
LIMITED WARRANTY	40 Year Limited Residential	5 Year Light Commercial
COUNTRY OF MANUFACTURE	Germany	

STANDARDS - MANUFACTURING & USAGE

	Performance	Test Method	Measure
EN 16511	Geometric properties	ISO 24337	Requirements According to Table 1 fulfilled
	Abrasion resistance	EN 15468 (Falling-Sand Method)	Exceeds requirements, > 6000 Revolutions
	Resistance against impact	EN 13329	Meets requirements, Big ball > 1800 mm
	Microscratch resistance	EN 16094	Meets requirements, MSR-A2/B2
	Effect of a castor chair	EN 425	Meets requirements, no visible change/damages
	Effect of a furniture leg	EN ISO 16581	Meets requirements, no visible change/damages
	Determination of static indentation	EN ISO 24343	Exceeds requirements
	Resistance against staining	EN 438-2	Exceeds requirements, Grade 5 for Groups 1, 2 & 3
	Locking strength	ISO 24334	Exceeds requirements
	Dimensional stability	EN ISO 23999	Exceeds requirements, Length 0.1% / Width 0.1%
ASTM F3261	Size, tol. ≥24 in. ≤48 in.	ISO 24337 - Tile, Plank	Meets and/or Exceeds
	Size, tol. ≥48 in.	ISO 24337 - Plank	Meets and/or Exceeds
	Thickness	ASTM F387	Meets and/or Exceeds
	Squareness	ISO 24337	Meets and/or Exceeds
	Flatness, max, inches (width & length)	ISO 24337	Meets and/or Exceeds
	Openings, avg / max, mm	ISO 24337	Meets and/or Exceeds
	Ledging, avg / max, mm	ISO 24337	Meets and/or Exceeds
	Residual indentation, in.	ASTM F1914	Meets and/or Exceeds
	Surface integrity	ASTM F1914	Meets and/or Exceeds
	Dimensional stability	ISO 23999 / F2199	Meets and/or Exceeds
	Curl, inches	ISO 23999 / F2199	Meets and/or Exceeds
	Resistance to chemicals	ASTM F925	Exceeds requirements, "0 - No Change"
	Resistance to heat	ASTM F1514	Exceeds requirements, Delta E Rating (ΔE) < 0.5
	Resistance to light	ASTM F1515	Exceeds requirements, Delta E (ΔE) Rating < 1.5
	Static Load	ASTM F970	Exceeds requirements, 800 psi 0.005" (0.13mm)

SUSTAINABILITY - GREENGUARD Gold Certified. This Standard includes health-based criteria to ensure that products are acceptable for use in environments such as schools and health care facilities. In addition to limiting emissions of more than 360 VOCs and total chemical emissions, comply with requirements of the state of California Department of Public Health (CDPH) Standard Method for the Testing and Evaluation of VOC Emissions from Indoor Sources Using Environmental Chambers, Version 1.1 (2010) (also known as California Section 01350 or CDPH v.1.1-2010)



www.blauer-enge.de/en/uz120

TECHNICAL INFORMATION & SPECIFICATIONS

GALLERY 5.0mm

**RECYCLABLE
100% PVC-FREE**

STANDARDS - MANUFACTURING & USAGE

	Performance	Test Method	Measure
SUPPLEMENTARY	R-value / Thermal Resistance	EN 12667	0.0312 (m ² K) / W
	Thickness Swelling	NALFA 3.2	Meets and/or Exceeds
	Surface Bond	NALFA 3.10	Meets and/or Exceeds
	Deflection	ASTM F1304	Meets and/or Exceeds
	Static Propensity (Step & Scuff)	AATCC 134	Maximum Average 3.6 kv Negative
	Slip resistance	EN 13893	μ = 0.40 class DS according to EN 14342
		ANSI / NFSI B101.3	≥ 0.35 DCOF Wet
		ASTM D2047 (leather wet)	≥ 0.5 SCOF Dry avg.
	Resistance to Fungi	ASTM G21	Rating 0 (Weeks 1-4 No Fungal Growth)
	Heavy Metals - Sb, As, Ba, Cd, Cr, Hg, Pb, Se	EN 15102 to DIN EN 71-3 and DIN EN 12149	Passes, Very Low or Not Detectable
	Asbestos Bulk Analysis	by PLM	Passes, Not Detectable
	Flammability	ASTM D2859	Passes, (face side)
	Smoke density	ASTM E662	Passes, ≤ 450 Flaming and Non-flaming
	Critical radiant flux	ASTM E648	Passes, Exceeds Class I
SOUND	Sound Transmission Class (STC)	ASTM E90 & E413, 6" Conc. Slab 8" Conc. Slab w/Drop Ceiling	Sound transmission class STC 50 dB Sound transmission class STC 62 dB
	Impact Insulation Class (IIC)	ASTM E492 & E989, 6" Conc. Slab 8" Conc. Slab w/Drop Ceiling	Impact insulation class IIC 57 dB High-Frequency Impact insulation class HIIC 61 dB Impact insulation class IIC 73 dB High-Frequency Impact insulation class HIIC 91 dB
	Delta Impact Insulation Class (ΔIIC)	ASTM E2179	Delta impact insulation class ΔIIC 25 dB Delta High-Frequency impact insulation class ΔHIIC 32 dB

SUSTAINABILITY - GREENGUARD Gold Certified. This Standard includes health-based criteria to ensure that products are acceptable for use in environments such as schools and health care facilities. In addition to limiting emissions of more than 360 VOCs and total chemical emissions, comply with requirements of the state of California Department of Public Health (CDPH) Standard Method for the Testing and Evaluation of VOC Emissions from Indoor Sources Using Environmental Chambers, Version 1.1 (2010) (also known as California Section 01350 or CDPH v.1.1-2010)



CERAMIN[®]
Inhaus[®] In partnership with **CLASSEN**[®]



www.blauer-enge.de/en/uz120

Effective: 24 Oct 2023

Note: This edition replaces all previous versions.

For additional assistance contact support at 1 888 255 3412 or visit inhausurfaces.com